

DEALER COLD WATER PRESSURE WASHERS

Aluminum Series

Electric | Hand Carry/Portable/Stationary | Direct Drive



This powerful electric pressure washer series is ideal for removing dirt, mud, mold and mildew from almost any surface. Contractors love it because the lightweight design makes it easy to move from one job to the next.



DC-1502-H0E1G



DC-1502-A0E1G shown with detergent injector, AW-8400-0021

Pump

- Direct drive triplex piston General pump with ceramic plungers
- External bypass system allows more water into the system to protect from heat build-up
- Stainless-steel and brass trapping unloader

Motor

- Low speed 1750 RPM

Frame

- Lightweight, corrosion-resistant aluminum frame and base plate with 1¼-inch tube handles (Portable models)
- 13-inch flat-free tires (10-inch on DC-1502-A0E1G) (Portable models)

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- External downstream detergent injector with detergent nozzle
- 50-foot x 3/8-inch non-marking high pressure hose (25-foot on DC-1502 models)
- 36-inch lance with rubber grip (48-inch on DC-3005-A0E2G)
- Professional-grade insulated “easy pull” trigger gun with safetylock-off



DEALER COLD WATER PRESSURE WASHERS

Aluminum Series

Electric | Hand Carry/Portable/Stationary | Direct Drive



Hand Carry Model

Model Number	PSI	GPM	Horsepower/Motor	Pump	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DC-1502-H0E1G	1500	2.0	2.0 HP, 120V, 1Ø, 18.8A	General	NEMA 5-20P	25x11x14in.	125 lb.	90 lb.

Portable Models

Model Number	PSI	GPM	Horsepower/Motor	Pump	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DC-1502-A0E1G	1500	2.0	2.0 HP, 120V, 1Ø, 18.8A	General	NEMA 5-20P	42.9x20.5x24.7in.	104 lb.	87 lb.
DC-2503-A0E2G	2500	3.2	6.0 HP, 230V, 1Ø, 24.1A	General	NEMA 6-30P	46.4x23.8x24.6in.	225 lb.	162 lb.
DC-3004-A0E2G	3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	General	NEMA 6-50P	46.4x23.8x24.6in.	257 lb.	194 lb.
DC-3005-A0E2G	3000	4.8	10.0 HP, 230V, 1Ø, 40.5A	General	NEMA 6-50P	51x26x24in.	335 lb.	285 lb.

Stationary Models

Model Number	PSI	GPM	Horsepower/Motor	Pump	Plug Type	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DC-1502-A0E1G-W*	1500	2.0	2.0 HP, 120V, 1Ø, 18.8A	General	NEMA 5-20P	24.5x10.8x12.2in.	108 lb.	73 lb.
DC-2503-A0E2G-W*	2500	3.2	6.0 HP, 230V, 1Ø, 24.1A	General	NEMA 6-30P	29.1x13.5x17.8in.	181 lb.	142 lb.
DC-3004-A0E2G-W*	3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	General	NEMA 6-50P	30.6x13.7x18.9in.	214 lb.	175 lb.

*Does not ship with handles or wheels, designed for wall mount applications.

Options:

Part Number	Description	Fits Models
CX-0005	36-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	DC-3005-A0E2G
CX-0030	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	DC-1502-H0E1G, DC-1502-A0E1G, DC-1502-A0E1G-W
CX-0104	Wall mount kit - Provides a permanent location for your pressure washer in a shop or plant facility	DC-1502-A0E1G-W
CX-0105	Wall mount kit - Provides a permanent location for your pressure washer in a shop or plant facility	DC-2503-A0E2G-W & DC-3004-A0E2G-W

Accessories:

Part Number	Description	Fits Models
18-0370	Rotating nozzle with lance - Increase your cleaning power and decrease your cleaning time, 2400-PSI rated, 1.25mm	DC-1502-H0E1G
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	DC-1502-H0E1G & DC-3005-A0E2G
851-0338	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	DC-3005-A0E2G
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	DC-3005-A0E2G




NEMA 5-20P,
20-amp plug



NEMA 6-30P,
30-amp plug



NEMA 6-50P,
50-amp plug



DC-1502-A0E1G-W shown with wall mount kit option, CX-0104

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.